

ACT-24T Digital Bodypack Transmitter

Key Features

- Miniature, sturdy plastic compact design.
- Mute button with Push & Talk function along with a LED status indicator. A connector for remote mute switch cable.
- Unique battery cover design provides easy access to operational controls and protects against accidental change of settings.
- Adjustable belt clip allows wearing transmitter in up or down position.
- Mini-XLR input with secure screw lock connector for lavalier / headworn mics and guitar.
- World's first ACT™ function provides precise and rapid frequency sync to the receiver.
- Selectable impedance for microphone or guitar / line inputs.

Microphone Capsules


MU-13	Single-sided Earworn Microphone (beige)
MU-23	Omni-directional Headworn Microphone (beige, fixed connector)
MU-23d	Omni-directional Headworn Microphone (beige, detachable cont)
MU-210	Uni-directional Headworn Microphone (beige, fixed connector)
MU-210d	Uni-directional Headworn Microphone (beige, detachable cont.)
MU-53L MU-53LS	Uni-directional Lavalier Microphone (black beige)
MU-55L MU-55LS	Omni-directional Lavalier Microphone (black beige)
MU-53HN MU-53HNS	Uni-directional Headworn Microphone (black beige)
MU-55HN MU-55HNS	Omni-directional Headworn Microphone (black beige)

Accessories

ASP-30	Neoprene Sports Pouch
MJ-70	Remote Mute Switch
MU-40G	Instrument Cable
TC-18	Transmitter Shielding Storage Case

Technical Specifications

Frequency Range	ISM 2.4 GHz
Channel Set-Up	ACT Sync
RF Output Power	2 mW / 10 mW switchable (country dependent)
Max. Audio Input	6.5 dBV
Mute Connector	Optional MJ-70 remote mute switch
Battery Meter	3 LEDs light in green to indicate battery status and turn to red to indicate low battery; after 2 hours power will automatically be shut down.
Battery Type	2 × AA alkaline
Current Consumption	Approx. 138 mA
Operating Time	Min. 10 hours
Dimensions (W × H × D)	63 × 82 × 22 mm
Net Weight	Approx. 75 g



MIPRO Electronics Co., Ltd

Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan
Tel: +886.5.238.0809 | Fax: +886.5.238.0803
www.mipro.com.tw | mipro@mipro.com.tw