ACT-500T UHF Analog Bodypack Transmitter

Features

- · Newly designed compact and lightweight housing for easy wearing.
- The panel integrates a backlit LCD and setup buttons for easy operation and view of all operating information, and a lockable power switch prevents the power switch from accidental operation.
- In addition to the power switch and the mute button, functions such as input sensitivity, power output, mute and button lock modes are also programmable.
- The world's first ACT™ function provides precise and rapid frequency sync to the receiver
- · 5 switchable gain levels.
- Mute button and remote-control jack allow quick setting of MUTE function.
- The patented battery compartment can be inserted with two AA-type batteries or one rechargeable Li-ion battery, charging via USB Type-C with the foolproof and safe charging circuit.
- · A belt clip for easy wearing.





Specifications

Bandwidth 24 MHz Display Backlit LCD Mic. Capsule Modules Work with all MIPRO's lavalier and headworn mics Input Connector MIPRO 4-Pin Mini XLR AF Sensitivity Preset at 0 dB (equal to capsule sensitivity) 5 switchable levels: -12 dB to 12 dB Max. Audio Input 0 dBV RF Power Output 10 mW / 50 mW switchable (country dependent) Spurious Emission < 4 nW Battery One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension 63 × 80 × 25 mm (W × H × D)	Frequency Range	UHF 480 – 934 MHz (country dependent)
Mic. Capsule Modules Input Connector MIPRO 4-Pin Mini XLR AF Sensitivity Preset at 0 dB (equal to capsule sensitivity) 5 switchable levels: -12 dB to 12 dB Max. Audio Input 0 dBV RF Power Output 10 mW / 50 mW switchable (country dependent) Spurious Emission A nW Battery One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension Work with all MIPRO's lavalier and headworn mics MIPRO 4-Pin Mini XLR Preset at 0 dB (equal to capsule sensitivity) 5 switchable levels: -12 dB to 12 dB (country dependent) V 4 nW Spurious Emission Spurious Emission Spurious Emission One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension One 18500 Li-ion battery One Dimension	Bandwidth	24 MHz
Input Connector AF Sensitivity Preset at 0 dB (equal to capsule sensitivity) 5 switchable levels: -12 dB to 12 dB Max. Audio Input 0 dBV RF Power Output 10 mW / 50 mW switchable (country dependent) Spurious Emission < 4 nW Battery One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension MIPRO 4-Pin Mini XLR Preset at 0 dB (equal to capsule sensitivity) 5 switchable (country dB Country dependent) < 4 nW USB Type-C Dimension MIPRO 4-Pin Mini XLR Preset at 0 dB (equal to capsule sensitivity) 5 switchable (country dependent) Country dependent) Spurious Emission 4 nW One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension	Display	Backlit LCD
AF Sensitivity Preset at 0 dB (equal to capsule sensitivity) 5 switchable levels: -12 dB to 12 dB Max. Audio Input 0 dBV RF Power Output 10 mW / 50 mW switchable (country dependent) Spurious Emission < 4 nW Battery One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension 63 × 80 × 25 mm (W × H × D)	Mic. Capsule Modules	Work with all MIPRO's lavalier and headworn mics
5 switchable levels: -12 dB to 12 dB Max. Audio Input 0 dBV RF Power Output 10 mW / 50 mW switchable (country dependent) Spurious Emission < 4 nW Battery One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension 63 × 80 × 25 mm (W × H × D)	Input Connector	MIPRO 4-Pin Mini XLR
Max. Audio Input 0 dBV RF Power Output 10 mW / 50 mW switchable (country dependent) Spurious Emission < 4 nW Battery One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension 63 × 80 × 25 mm (W × H × D)	AF Sensitivity	Preset at 0 dB (equal to capsule sensitivity)
RF Power Output 10 mW / 50 mW switchable (country dependent) Spurious Emission < 4 nW Battery One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension 63 × 80 × 25 mm (W × H × D)		5 switchable levels: -12 dB to 12 dB
Spurious Emission < 4 nW Battery One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension 63 × 80 × 25 mm (W × H × D)	Max. Audio Input	0 dBV
Battery One 18500 Li-ion battery or two AA alkaline Charging USB Type-C Dimension 63 × 80 × 25 mm (W × H × D)	RF Power Output	10 mW / 50 mW switchable (country dependent)
Charging USB Type-C Dimension 63 × 80 × 25 mm (W × H × D)	Spurious Emission	< 4 nW
Dimension 63 × 80 × 25 mm (W × H × D)	Battery	One 18500 Li-ion battery or two AA alkaline
	Charging	USB Type-C
	Dimension	63 × 80 × 25 mm (W × H × D)
Weight Approx. 96 g	Weight	Approx. 96 g
Note Refer to the actual product in the event of product discrepancy	Note	Refer to the actual product in the event of product discrepancy

