


ACT-700T UHF Analog Wideband Bodypack Transmitter

Features

- Newly designed compact and lightweight housing for easy wearing.
- The panel integrates a backlit LCD and setup buttons for easy operation and view of all operating information, and a lockable power switch prevents the power switch from accidental operation.
- In addition to the power switch and the mute button, functions such as input sensitivity, low frequency reduction, volume limit, power output, and button lock modes are also programmable.
- The world's first ACT™ function provides precise and rapid frequency sync to the receiver
- 5 switchable gain levels.
- Mute button and remote-control jack allow quick setting of MUTE function.
- The patented battery compartment can be inserted with two AA-type batteries or one rechargeable Li-ion battery, charging via USB Type-C with the foolproof and safe charging circuit. The second-generation ACT-700T features charging contacts and can also be placed on an optional single-slot or dual-slot charging station for charging.
- A belt clip for easy wearing.



Specifications

| | |
|----------------------|---|
| Frequency Range | UHF 480 – 934 MHz (country dependent) |
| Bandwidth | 72 MHz |
| Display | Backlit LCD |
| Mic. Capsule Modules | Work with all MIPRO's lavalier and headworn mics |
| Input Connector | MIPRO 4-Pin Mini XLR |
| AF Sensitivity | Preset at 0 dB (equal to capsule sensitivity) 5 switchable levels: -12 dB to 12 dB |
| Max. Audio Input | 0 dBV |
| RF Power Output | 10 mW / 50 mW switchable (country dependent) |
| Spurious Emission | < 4 nW |
| Battery Type | One 18500 Li-ion battery or two AA alkaline |
| Battery Charging | MP-800 / MP-820 charging station or USB Type-C |
| Dimensions | 63 × 80 × 25 mm (W × H × D) |
| Weight | Approx. 97 g |