## **MA-300 Portable Wireless PA System**


## **Features**

- The two-way speaker cabinet is redesigned to improve the efficiency in treble frequency and delivers a clear and powerful sound effect for both speech and music.
- Easy hand-carrying or stand-mounting makes MA-300 the most ideal megaphone for various applications.
- One UHF or ISM 5.8 GHz band receiver module for longdistance and reliable reception performance.
- Plug-in Bluetooth module, USB player/recorder, built-in echo function, and alarm siren which has a fade-in effect.
- Equipped with audio input mixer. Each audio source has individual volume control.
- Removable Li-ion battery holder for fast insertion and replacement.
- Bluetooth with TWS technology can combine two megaphones for stereo sound.









## **Specifications**

Drivers  1" Treble & 5" Woofer  Frequency Range  80 Hz – 18 kHz  Audio Inputs  MIC IN: 1 × 1/4" (6.3 mm)  LINE IN: 1 × 1/8" (3.5 mm)  Audio Output  LINE OUT: 1 × 1/8" (3.5 mm)  Amplifier  Class D  Output Power  60 W RMS, 102 W peak  Receiver Module  1 × UHF or ISM 5.8 GHz module  Audio Players  Plug-in Bluetooth module & USB recorder / player  Other Functions  Echo on mics & siren sound effect  Power Supply  DC (19 – 24 V) socket for external AC (100 – 240 V) power supply  Battery  4 × 18650 Li-ion batteries (MB-14)  Battery Indicator  4-segment indicator (25/50/75/100%)  Standby Time  Up to 10 hours  Dimensions  209 × 278 × 165 mm (W × H × D)  Weight  Approx. 2.7 kg (batteries included)  Optional Accessories  Patents and Approvals  Patented. Telecom and safety regulations approved  Note  Refer to the actual product in the event of product description discrepancy	Max. SPL	105 dB
Frequency Range 80 Hz – 18 kHz  Audio Inputs MIC IN: 1 × 1/4" (6.3 mm)  LINE IN: 1 × 1/8" (3.5 mm)  Audio Output LINE OUT: 1 × 1/8" (3.5 mm)  Amplifier Class D  Output Power 60 W RMS, 102 W peak  Receiver Module 1 × UHF or ISM 5.8 GHz module  Audio Players Plug-in Bluetooth module & USB recorder / player  Other Functions Echo on mics & siren sound effect  Power Supply DC (19 – 24 V) socket for external AC (100 – 240 V) power supply  Battery 4 × 18650 Li-ion batteries (MB-14)  Battery Indicator 4-segment indicator (25/50/75/100%)  Standby Time Up to 10 hours  Dimensions 209 × 278 × 165 mm (W × H × D)  Weight Approx. 2.7 kg (batteries included)  Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones  Patents and Approvals		
Audio Inputs  MIC IN: 1 × 1/4" (6.3 mm)  LINE IN: 1 × 1/8" (3.5 mm)  Audio Output  LINE OUT: 1 × 1/8" (3.5 mm)  Amplifier  Class D  Output Power  60 W RMS, 102 W peak  Receiver Module  1 × UHF or ISM 5.8 GHz module  Audio Players  Plug-in Bluetooth module & USB recorder / player  Other Functions  Echo on mics & siren sound effect  Power Supply  DC (19 - 24 V) socket for external AC (100 - 240 V) power supply  Battery  4 × 18650 Li-ion batteries (MB-14)  Battery Indicator  Standby Time  Up to 10 hours  Dimensions  209 × 278 × 165 mm (W × H × D)  Weight  Approx. 2.7 kg (batteries included)  Optional Accessories  Patents and Approvals  Patented. Telecom and safety regulations approved		
LINE IN: 1 × 1/8" (3.5 mm)  Audio Output LINE OUT: 1 × 1/8" (3.5 mm)  Amplifier Class D  Output Power 60 W RMS, 102 W peak  Receiver Module 1 × UHF or ISM 5.8 GHz module  Audio Players Plug-in Bluetooth module & USB recorder / player  Other Functions Echo on mics & siren sound effect  Power Supply DC (19 – 24 V) socket for external AC (100 – 240 V) power supply  Battery 4 × 18650 Li-ion batteries (MB-14)  Battery Indicator 4-segment indicator (25/50/75/100%)  Standby Time Up to 10 hours  Dimensions 209 × 278 × 165 mm (W × H × D)  Weight Approx. 2.7 kg (batteries included)  Optional Accessories Patents and Approvals  Patented. Telecom and safety regulations approved	Frequency Range	****
Audio Output LINE OUT: 1 × 1/8" (3.5 mm)  Amplifier Class D  Output Power 60 W RMS, 102 W peak  Receiver Module 1 × UHF or ISM 5.8 GHz module  Audio Players Plug-in Bluetooth module & USB recorder / player  Other Functions Echo on mics & siren sound effect  Power Supply DC (19 – 24 V) socket for external AC (100 – 240 V) power supply  Battery 4 × 18650 Li-ion batteries (MB-14)  Battery Indicator 4-segment indicator (25/50/75/100%)  Standby Time Up to 10 hours  Dimensions 209 × 278 × 165 mm (W × H × D)  Weight Approx. 2.7 kg (batteries included)  Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones  Patents and Approvals	Audio Inputs	MIC IN: 1 × 1/4" (6.3 mm)
Amplifier Class D  Output Power 60 W RMS, 102 W peak  Receiver Module 1 × UHF or ISM 5.8 GHz module  Audio Players Plug-in Bluetooth module & USB recorder / player  Other Functions Echo on mics & siren sound effect  Power Supply DC (19 – 24 V) socket for external AC (100 – 240 V) power supply  Battery 4 × 18650 Li-ion batteries (MB-14)  Battery Indicator 4-segment indicator (25/50/75/100%)  Standby Time Up to 10 hours  Dimensions 209 × 278 × 165 mm (W × H × D)  Weight Approx. 2.7 kg (batteries included)  Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones  Patents and Approvals  Patented. Telecom and safety regulations approved		LINE IN: 1 × 1/8" (3.5 mm)
Output Power60 W RMS, 102 W peakReceiver Module1 × UHF or ISM 5.8 GHz moduleAudio PlayersPlug-in Bluetooth module & USB recorder / playerOther FunctionsEcho on mics & siren sound effectPower SupplyDC (19 – 24 V) socket for external AC (100 – 240 V) power supplyBattery4 × 18650 Li-ion batteries (MB-14)Battery Indicator4-segment indicator (25/50/75/100%)Standby TimeUp to 10 hoursDimensions209 × 278 × 165 mm (W × H × D)WeightApprox. 2.7 kg (batteries included)Optional AccessoriesSC-300 carry bag, MS-30 tripod stand, MM Series microphonesPatents and ApprovalsPatented. Telecom and safety regulations approved	Audio Output	LINE OUT: 1 × 1/8" (3.5 mm)
Receiver Module 1 × UHF or ISM 5.8 GHz module  Audio Players Plug-in Bluetooth module & USB recorder / player  Other Functions Echo on mics & siren sound effect  Power Supply DC (19 – 24 V) socket for external AC (100 – 240 V) power supply  Battery 4 × 18650 Li-ion batteries (MB-14)  Battery Indicator 4-segment indicator (25/50/75/100%)  Standby Time Up to 10 hours  Dimensions 209 × 278 × 165 mm (W × H × D)  Weight Approx. 2.7 kg (batteries included)  Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones  Patents and Approvals Patented. Telecom and safety regulations approved	Amplifier	Class D
Audio Players Plug-in Bluetooth module & USB recorder / player  Other Functions Echo on mics & siren sound effect  Power Supply DC (19 – 24 V) socket for external AC (100 – 240 V) power supply  Battery 4 × 18650 Li-ion batteries (MB-14)  Battery Indicator 4-segment indicator (25/50/75/100%)  Standby Time Up to 10 hours  Dimensions 209 × 278 × 165 mm (W × H × D)  Weight Approx. 2.7 kg (batteries included)  Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones  Patents and Approvals Patented. Telecom and safety regulations approved	Output Power	60 W RMS, 102 W peak
Other Functions	Receiver Module	1 × UHF or ISM 5.8 GHz module
Power Supply DC (19 – 24 V) socket for external AC (100 – 240 V) power supply  Battery 4 × 18650 Li-ion batteries (MB-14)  Battery Indicator 4-segment indicator (25/50/75/100%)  Standby Time Up to 10 hours  Dimensions 209 × 278 × 165 mm (W × H × D)  Weight Approx. 2.7 kg (batteries included)  Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones  Patents and Approvals Patented. Telecom and safety regulations approved	Audio Players	Plug-in Bluetooth module & USB recorder / player
Battery 4 × 18650 Li-ion batteries (MB-14)  Battery Indicator 4-segment indicator (25/50/75/100%)  Standby Time Up to 10 hours  Dimensions 209 × 278 × 165 mm (W × H × D)  Weight Approx. 2.7 kg (batteries included)  Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones  Patents and Approvals Patented. Telecom and safety regulations approved	Other Functions	Echo on mics & siren sound effect
Battery Indicator 4-segment indicator (25/50/75/100%)  Standby Time Up to 10 hours  Dimensions 209 × 278 × 165 mm (W × H × D)  Weight Approx. 2.7 kg (batteries included)  Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones  Patents and Approvals Patented. Telecom and safety regulations approved	Power Supply	DC (19 – 24 V) socket for external AC (100 – 240 V) power supply
Standby TimeUp to 10 hoursDimensions209 × 278 × 165 mm (W × H × D)WeightApprox. 2.7 kg (batteries included)Optional AccessoriesSC-300 carry bag, MS-30 tripod stand, MM Series microphonesPatents and ApprovalsPatented. Telecom and safety regulations approved	Battery	4 × 18650 Li-ion batteries (MB-14)
Dimensions 209 × 278 × 165 mm (W × H × D)  Weight Approx. 2.7 kg (batteries included)  Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones  Patents and Approvals Patented. Telecom and safety regulations approved	Battery Indicator	4-segment indicator (25/50/75/100%)
Weight Approx. 2.7 kg (batteries included) Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones Patents and Approvals Patented. Telecom and safety regulations approved	Standby Time	Up to 10 hours
Optional Accessories SC-300 carry bag, MS-30 tripod stand, MM Series microphones Patents and Approvals Patented. Telecom and safety regulations approved	Dimensions	209 × 278 × 165 mm (W × H × D)
Patents and Approvals Patented. Telecom and safety regulations approved	Weight	Approx. 2.7 kg (batteries included)
	Optional Accessories	SC-300 carry bag, MS-30 tripod stand, MM Series microphones
Note Refer to the actual product in the event of product description discrepancy	Patents and Approvals	Patented. Telecom and safety regulations approved
	Note	Refer to the actual product in the event of product description discrepancy