
MA-708 Luxury Portable PA

Features

- One-piece molded cabinet with high-efficiency amplifier system to drive the dual speaker system for powerful and clear sound.
- Retractable handle and rugged wheels make it amazingly easy to transport. It can be hand-carried or installed on a tripod stand.
- Built-in transmitters' storage
- Modularized optional accessories for fast and easy installation and replacement.
- TONE, VOP (voice-over-priority) and ECHO control on mics.
- Mixed input amplification of wired mic, wireless mic, and audio players.
- Extension speaker socket can be used with MA-708EXP passive speaker.
- Industry's only wireless interlinking transmitter option to interlink multiple MA-708 portables wirelessly to extend transmission range and expand coverage.
- Industry's first built-in active dual antennas for long distance and stable receiving.
- Built-in AC switching power supply and rechargeable batteries.







Specifications

Maximum SPL	108 dB
Loudspeakers	1.5" Tweeter & 8" Woofer
Frequency Range	50 Hz – 18 kHz
Audio Inputs	MIC IN: 1 × XLR, 1 × 1/4" (6.3 mm)
	LINE IN: 1 × RCA
Audio Output	LINE OUT: 1 × RCA
Amplifier	Class D
Output Power	190 W RMS, 325 W peak
Receiver Modules	Up to 4
Audio Players	Bluetooth, CD/USB/SD player & recorder (optional)
Transmitter Modules	MTM-92 (optional)
Extension Speaker	1 × 1/4" (6.3 mm)
Other Functions	TONE, VOP and ECHO control on mics
Power Supply	AC 100 – 240 V or DC 24 – 32 V
Battery Type	Built-in Lead-acid battery
Standby Time	Up to 7 hours
Battery Indicator	4-segment indicators (25/50/75/100%)
Color	Black
Dimensions	336 × 545 × 336 mm / 13.2" × 21.5" × 13.2" (W×H×D)
Weight	Approx. 15.3 kg / 33.7 lb. (weight varies depending on product configuration)
Optional Accessories	SC-708 carry bag, MS-70 tripod stand, MM-Series microphones, MB-80 Li-ion battery
Patents	Patented. Telecom and safety regulations approved.
Note	Refer to the actual product in the event of product description discrepancy.

