


# MI-24R Digital Stereo Bodypack Receiver

## Features

- The MI-24 Series digital wireless IEM system operates in ISM 2.4 GHz band and presets 8 channels. Simple functions and operations for the personal user market.
- The MI-24 adapts a 24 bit / 48 kHz sample rate. The main features are similar to the MI-58 system. However, the MI-24R receiver adds EARDRIVE to enhance the performance of earphones and the audio latency is < 3.5 ms, thus can satisfy the demanding music listening.
- Before, the MI-909 Series UHF IEM system cannot deliver the best sound quality due to the telecom regulation's restrictions. Now the MI-24 system has the advantages of the frequency band, sound quality and price, so it is the best choice of the wireless IEM system.



## Specifications

Housing	Industry's smallest reinforced plastic case.
Display	Backlit graphic LCD
Frequency Range	ISM 2.4 GHz (2,400 ~ 2,483.5 MHz)
Modulation Type	Digital modulation
Channel Setting	ACT sync
Receiving Mode	True diversity receiving
Frequency Response	20 Hz ~ 23 kHz (stereo)
Stereo Separation	> 100 dB
Max. S/N Ratio	> 109 dBA
T.H.D	< 0.1% at 1 kHz
Sensitivity	5 $\mu$ V input level, S/N > 100 dB (stereo).
Earphone Jack	$\varnothing$ 3.5 mm stereo phone jack, Left / Right $\times$ 100 mW @ 16 $\Omega$ .
Power Supply	ICR18500 Li-ion rechargeable battery $\times$ 1. Current drain 140 mA. Up to 9 hours of continuous use.
Charger	MP-8 one-slot charging station
Optional Accessories	E-8S or E-8P earphones
Note	Refer to the actual product in the event of product discrepancy.



### MIPRO Electronics Co., Ltd

Headquarters: 814 Beigang Road, Chiayi, 600079, Taiwan  
Tel: +886.5.238.0809 | Fax: +886.5.238.0803  
www.mipro.com.tw | mipro@mipro.com.tw

Specifications are subject to change without prior notice. MI021/08