
MI-24R 2.4 GHz Digital Stereo Bodypack Receiver

Features

- The MI-24 Series digital wireless IEM system operates in ISM 2.4 GHz band and presets 8 channels. Simple functions and operations for the personal user market.
- The MI-24R adds EAR DRIVE to enhance the performance of earphones and the audio latency is < 3.5 ms, thus satisfying the demanding music listeners.
- Stereo / Mono / Mixed output modes and EQ settings to suit the users' preferences.
- A Ø 3.5 mm TRS jack provides left/right 100 mW @16 Ω output for earphones.
- Optional standard or professional Ø 3.5 mm TRS noise isolating earphones are available.





Specifications

| Housing | Glass-fiber reinforced plastic |
|----------------------|---|
| Display | Backlit LCD |
| Frequency Band | ISM 2.4 GHz |
| Modulation Type | Digital modulation |
| Channel Setting | ACT™ sync |
| Receiving Mode | True diversity |
| Latency | < 3.5 ms |
| Frequency Response | 20 Hz – 23 kHz (stereo) |
| Stereo Separation | > 100 dB |
| S/N Ratio | 109 dBA |
| THD | < 0.1% @ 1 kHz |
| Sensitivity | 5 μV input level, S/N > 100 dB |
| Earphone Jack | 3.5 mm TRS |
| Battery | One 18500 Li-ion battery |
| Charger | MP-8 |
| Optional Accessories | E-8S or E-8P earphones |
| Dimensions | 63 × 85 × 26 mm (W × H × D) |
| Weight | Approx. 82 g |
| Note | Refer to the actual product in the event of product description discrepancy |

