


MI-24R 2.4 GHz Digital Stereo Bodypack Receiver

Features

- Stereo / Mono / Mixed output modes.
- EQ settings to suit the users' preferences.
- A \varnothing 3.5 mm TRS jack provides left/right 100 mW @16 Ω output for earphones. Optional standard or professional noise isolating earphones are available.
- Adds EAR DRIVE to enhance the performance of earphones and the audio latency is < 3.5 ms, thus satisfying the demanding music listeners.



Specifications

Housing	Glass-fiber reinforced plastic
Display	Backlit LCD
Frequency Band	ISM 2.4 GHz
Modulation Type	Digital modulation
Channel Setting	ACT™ sync
Receiving Mode	True diversity
Latency	< 3.5 ms
Frequency Response	20 Hz – 23 kHz (stereo)
Stereo Separation	> 100 dB
S/N Ratio	109 dBA
THD	< 0.1% @ 1 kHz
Sensitivity	5 μ V input level, S/N > 100 dB
Earphone Jack	3.5 mm TRS
Battery Type	One 18500 Li-ion battery
Battery Charging	MP-8 single-slot charging station
Optional Accessories	E-8S or E-8P earphones
Dimensions	63 × 85 × 26 mm (W × H × D)
Weight	Approx. 82 g



MIPRO Electronics Co., Ltd

Headquarters: 814 Beigang Road, Chiayi, 600079, Taiwan
Tel: +886.5.238.0809 | Fax: +886.5.238.0803
www.mipro.com.tw | mipro@mipro.com.tw

Specifications are subject to change without prior notice. CE024/02