


ACT-700H

UHF Analog Wideband Handheld Transmitter

FEATURES

- MIPRO's analog wideband handheld transmitter designed for the ACT-700 Series receivers, ensuring stable and reliable performance.
- Ergonomic matte black metal housing offers a comfortable grip, ultra-low handling noise, and a professional, understated appearance.
- Patented multifunction control module integrates the power switch, mute, setting keys, LCD display, and a locking slider to prevent accidental operation.
- Equipped with a uniquely designed capsule module—removable upper grille for cleaning and threaded lower grille for protection against impact, rolling, and pop noise.
- Standard with MU-90A supercardioid condenser capsule module; supports interchangeable MIPRO condenser or dynamic capsule modules and compatible ones from other brands.
- Supports essential functions including mute mode, input sensitivity, and RF output power with clear, user-friendly display.
- Five-stage gain adjustment ensures optimal audio input across varying vocal applications.
- Incorporates MIPRO's exclusive ACT™ function for quick and accurate frequency synchronization.
- Patented dual-purpose battery compartment allows easy switching between AA and rechargeable Li-ion batteries.
- Built-in USB Type-C charging port and charging contacts with protection circuitry support both cable and drop-in charging.
- Lower housing features a replaceable color-coded ID ring for channel identification. A patented antenna cover houses a high-efficiency wideband transmitting antenna.



SPECIFICATIONS

Frequency Range	UHF 480–934 MHz (country dependent)
Bandwidth	72 MHz
Display	Backlit LCD displays channel, battery status and setting menu
Control Interface	ACT sync sensor, setting buttons and mute button
Mic. Capsule Modules	MU-90A condenser or other compatible capsule modules
Audio Control	AF Gain
Gain Setting	-6 dB to +6 dB / 3 dB per segment
RF Power Output	10 mW / 50 mW switchable (country dependent)
Power Supply	One 18500 Li-ion battery or two AA alkaline
Battery Charging	MP-800 / MP-820 charging dock or USB Type-C
Dimensions	51 × 272 mm (Ø × L)
Weight	Approx. 330 g