



BC-100 II

Boundary Microphone Base

FEATURES

- Built-in 10 mm cardioid condenser capsule enables direct use as a boundary microphone, ideal for conferences and presentations.
- Compatible with MM Series 4-Pin gooseneck microphones, offering both wired and wireless transmission modes.
- In wired mode, the base output connects to a mixer with phantom power for stable, high-quality audio output.
- In wireless mode, the ACT-TC Series bodypack transmitter can be installed to convert into a wireless conference microphone, with direct charging on the base—no need to remove the transmitter.
- TALK / MUTE buttons allow synchronized control of LED indicators on both the base and the gooseneck microphone for efficient speech management.
- Metal base with anti-slip pads ensures stability and prevents wobbling during use.



SPECIFICATIONS

Boundary Microphone	10 mm cardioid condenser microphone capsule module
Input Jack	MIPRO 4-Pin XLR, compatible with MM-206L / MM-205L / MM-204L gooseneck microphone (optional)
Output Jack	3-Pin XLR
Control Interface	TALK / MUTE button, Boundary / Gooseneck switch
Wireless Function	Supports ACT-TC series bodypack transmitters (optional)
Power Supply	DC 24 – 48 V phantom power (wired mode) ; one 18500 Li-ion battery (wireless mode)
Charging Voltage	DC 5 V / 1 A
Dimensions	100 × 78 × 150 mm (W × H × D)
Weight	Approx. 620 g