


# MI-24T

## 2.4 GHz Digital Stereo Transmitter

### FEATURES

- Compact and versatile, the MI-24T operates in the license-free ISM 2.4 GHz band with 8 selectable channels—ideal for entry-level monitoring or small-scale events.
- Low-latency digital encoding (<3.5 ms) ensures precise, real-time monitoring when paired with compatible receivers.
- Supports 48 kHz / 24-bit digital audio for detailed, high-quality sound reproduction.
- Each channel can be assigned 1–64 user IDs and paired quickly via MIPRO's ACT automatic synchronization.
- OLED display and jog wheel provide a clear, intuitive interface with a lock function to prevent accidental adjustments.
- XLR / 6.3 mm combo input supports balanced and unbalanced sources; 6.3 mm LOOP OUT allows easy daisy-chaining to other devices.
- Includes 6.3 mm and 3.5 mm headphone outputs with adjustable volume for on-the-spot monitoring.



### SPECIFICATIONS

Chassis	Half-rack (9.5") metal chassis
Display	Graphic OLED
Control Interface	Rotary knob, ACT sync button, earphone volume control, AF input gain setting buttons
Frequency Response	ISM 2.4 GHz
Channels	Presets 8 channels
Encryption	64 ID codes are allowed to be set for each channel.
Modulation Type	Digital modulation
Audio Sampling	48 kHz / 24-bit
RF Power Output	< 10 mW (country dependent)
Frequency Response	20 Hz – 23 kHz (stereo)
Dynamic Range	≥ 109 dBA (system)
THD	< 0.1% @1 kHz
Max. Input Level	+24 dBu
Audio Inputs	2 × XLR / 6.3 mm TRS combo socket
Audio Outputs	2 × 6.3 mm TRS (Loop Out)
Earphone Jacks	1 × 6.3 mm and 1 × 3.5 mm TRS
Network Interface	Dante (optional)
Management Interface	RJ-11 × 2
Antenna Output	50 Ω TNC female connector
Power Supply	DC 12–15 V. External AC 100–240 V switching power supply
Dimensions	210 × 44 × 91 mm (W × H × D)
Weight	Approx. 580 g