

# TA-80

## UHF Digital Plug-on Transmitter

### FEATURES

- Full aluminum alloy housing provides superior durability and excellent RF shielding for reduced interference.
- Digital transmission technology ensures high audio quality, low latency, and strong anti-interference performance, ideal for professional stage and studio applications.
- Color LCD screen displays channel, battery, and signal status with intuitive operation.
- XLR audio input compatible with most professional dynamic and condenser microphones.
- Supports 12 V or 48 V phantom power to drive a wide range of condenser microphones.
- Selectable RF power output of 10 / 50 mW allows flexible adjustment to match different environments.
- Equipped with a replaceable 18500 lithium battery offering 5–8 hours of use, chargeable via MP-8T charging dock or external charger.



### SPECIFICATIONS

Frequency Range	UHF 480 – 934 MHz (country dependent)
RF Power Output	10 mW / 50 mW switchable (country dependent)
Audio Control	AF Gain, Low Cut, AF Limiter and Input Polarity
Audio Input	XLR female
Max Input	6 dBV (2 Vrms) @ 0 dB
Phantom Power	+12 V / +48 V at 10 mA max.
Gain Control	-18 dB to +30 dB, in 6 dB steps
Control Interface	ACT sync sensor, setting buttons and mute button
Display	Backlit LCD
Power Supply	One 18500 Li-ion battery
Battery Charging	MP-8T charging dock
Dimensions	44 × 114 × 39 mm (W × H × D)
Weight	Approx. 180 g

